

Product Name:	Bluelab Conductivity Pen
Product Code:	PENCON
UPC Code:	9421024920277
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	Sold as singular unit
Packaging Information:	
Packaged Weight:	0.134 kg / 0.295 lb
Packaged Length:	205 mm / 8.07 in
Packaged Width:	55 mm / 2.165 in
Packaged Height:	32 mm / 1.26 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The ultimate handy solution for measuring conductivity

The go-to for hand held conductivity meters.

The Bluelab® Conductivity Pen simply tells you the amount of nutrient in your solution. Conductivity is automatically compensated with the integrated temperature sensor.

Providing a compact, quick and accurate way to measure two key parameters for crop health.

Teamed with our Bluelab® pH Pen you have a robust, convenient and accurate measurement system.

Features:

- Measures conductivity and temperature
- Selectable units for conductivity and temperature
- Shows conductivity scales CF, EC, PPM 500 & PPM 700 at the touch of a button
- Fully waterproof
- Backlit LCD display
- Calibration optional
- Successful 30 day calibration indicator
- Hold reading function
- Low battery indicator
- Auto off function
- Automatic temperature compensation
- 1x AAA replaceable battery included

Product Guarantee:

One year free repair or replacement guarantee.



Product Image:



Product images available for Screen or Web use:

- Bluelab-ConductivityPen-MR-flat-RGB.jpg
- Bluelab- ConductivityPen -WEB.jpg
- Bluelab- ConductivityPen -Web-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab- ConductivityPen -MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 10.0 EC, 0 – 100 CF 0 – 5000 ppm (500 ppm / TDS) 0 – 7000 ppm (700 ppm) 0 – 50 °C / 32 – 122 °F
Resolution:	0.1 EC, 1 CF 10 ppm (500 ppm) 10 ppm (700 ppm) 1 °C / 1 °F
Accuracy at 2.77 EC and 25°C / 77°F:	± 0.1 EC, ± 1 CF ± 50 ppm (500 ppm) ± 70 ppm (700 ppm) ± 1 °C / ± 2 °F
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50 °C / 32 – 122 °F
Calibration:	Optional
Power Source:	1 x AAA alkaline battery
User Manual Languages Available:	English; Español; Français - Canada
Certifications:	CE and FCC

{This Product Information Sheet is NOT intended for distribution to end users.}